

EXPANDER

INPUT: +6dB, 0dB, -6dB, LEVEL

50Hz HI-PASS

G.R. 40 30 20 10 0dB

IN OUT

THRESHOLD: -10, 0, +10, -20, -30, -40, -50, dB

RATIO: 1:2, 1:5, 1:20

RELEASE: .5, 1, 2, .05, Sec., 5

FILTER

MAN AUTO

ATTN. -10dB, -20, -40dB

THRESHOLD: -10, 0, +10, -20, -30, -40, -50, dB

RATIO: 1:2, 1:5, 1:20

RELEASE: .5, 1, 2, .05, Sec., 5

EXPANDER

INPUT: +6dB, 0dB, -6dB, LEVEL

50Hz HI-PASS

G.R. 40 30 20 10 0dB

IN OUT

THRESHOLD: -10, 0, +10, -20, -30, -40, -50, dB

RATIO: 1:2, 1:5, 1:20

RELEASE: .5, 1, 2, .05, Sec., 5

FILTER

MAN AUTO

ATTN. -10dB, -20, -40dB

THRESHOLD: -10, 0, +10, -20, -30, -40, -50, dB

RATIO: 1:2, 1:5, 1:20

RELEASE: .5, 1, 2, .05, Sec., 5

DRAWMER

DUAL NOISE FILTER DF320

BYPASS NORM

STEREO LINK

POWER ON