D-510

D-558

D-590

DYNAMIC MICROPHONES WITH FLEXIBLE SHAFT FOR PUBLIC ADDRESS, PAGING AND INTERCOMMUNICATIONS SYSTEMS.

AKG D-510, D-558 and D-590

Specifically designed for optimum performance in sound systems for—

Auditoriums
Assembly Hall
Meeting Rooms
Churches
Schools
Hospitals
Banks
Industrial Plants
Sports Arenas
Studio Intercom
TV and Radio Broadcast

Microphones are delivered with mounting hardware for desk or table top mounting. Also available are 3 weighted table stands:


ST-4A Table Stand

ST-41 Table Stand with one push button, and pilot lamp

ST-43 Table Stand with three push buttons, and pilot lamp.

AKG

A complete range of professional condenser and dynamic microphones, headphones and boom sets.



TECHNICAL DATA

ing hardware.

Sensitivity : —56 db (re/1 mw/10 dynes/cm²)

Impedance: 200 ohms.


Dimensions: 123/16" lg., including shaft


at the end of the shaft or through the bot-

tom. Microphone is supplied with mount-

7/8" dia. at largest point

Net Weight: —9 oz





Accessories: See back page.

Differe dynam

For ap ent no pressu noise

An effuse of doors.

The D noisele direct

Supplion ductor hardw

TECH

D 510 5

Sensiti Imped Dimer

Net W



Acces



Differential, noise-cancelling dynamic microphone.

For applications in areas with high ambient noise levels. The differential acoustic pressure principle suppresses background noise and effectively cancels feedback.

An effective integral windscreen permits use of the unit indoors as well as outdoors.

The D-558 is equipped with 87/8" long noiseless flexible shaft and is suitable for direct mounting on flat surfaces.

Supplied with prewired, concealed 2-conductor plus shield cable and mounting hardware.


TECHNICAL DATA

Sensitivity: —60 db (re/1 mw/10 dynes/cm²)

Impedance: 200 ohms.

 $12^3/_{16}$ " lg., including shaft $^7/_8$ " dia. at largest point Dimensions:

Net Weight: --9 oz





Cardioid dynamic microphone

Excellent cardioid characteristics prevent feedback even under acoustically unfavorable conditions. Attenuated low end of the response range defeats low frequency oscillation and table-born noise,

Integral sintered bronze screen eliminates the disturbing effects of breath noise and wind turbulence.

The D-590 comes complete with 87/8" long noise-free, rugged flexible shaft, with prewired cable and standard 5/8"-27 thread for surface mounting.


TECHNICAL DATA

Sensitivity -55 db (re/1 mw/10 dynes/cm²)

Impedance: 200 ohms.

11½" lg., including shaft 15/8" dia. at largest point Dimensions:

Net Weight: -9 oz



Accessories: See back page.

accessories

for AKG D-510, D-558 and D-590

TABLE STANDS




Weighted table stand



24-30V (1) 2W 12 11 10 9 8 7 6 5 4 3 2 7

ST-41 Weighted table stand with one push-to-talk button and pilot lamp



ST-43

Weighted table stand with three push-to-talk buttons and pilot lamp





CLAMPS

Knock-out tabs




Clamp Adaptor



Flange





Windscreen for D-510 and D-558





Windscreen for D-590

MOUNTING SUGGESTIONS











AKG MICROPHONES · HEADPHONES

DISTRIBUTED BY
NORTH AMERICAN PHILIPS CORPORATION
100 EAST 42nd STREET, NEW YORK, NEW YORK 10017
TEL: (212) 697-3600 TWX: 212 867-5624